



GRID TIE INVERTER



Harness the **power of the sun** and never look back with our **solar inverters**



Max. Efficiency
98.5%



Low startup
DC voltage



Max. DC
overloading 30%



wide AC
voltage range



Type-II SPD Enabled
AC and DC Side



Eastman Solar App
for Remote
Monitoring 24x7



Built in zero
export function



IP 65
Enclosure

GRID TIE INVERTER - SINGLE PHASE

Model	EGT-3K-1P1M	EGT-5K-1P2M
Input (DC)		
Max. DC Input Power (kW)	3.9	6.5
Max. DC Input Voltage (V)	550	
Start-up DC Input Voltage (V)	80	
MPPT Operating Range (V)	70~500	
Max. DC Input Current (A)	13	13+13
Max. Short Circuit Current (A)	19.5	19.5+19.5
No.of MPP Trackers	1	2
No.of Strings per MPP Tracker	1	
Output (AC)		
Rated Output Power (kW)	3	5
Max. Active Power (kW)	3.3	5.5
Nominal Output Voltage / Range (V)	L/N/PE 220/230V (Optional)	
Rated Grid Frequency (Hz)	50 / 60 (Optional)	
Operating Phase	Single phase	
Rated AC Grid Output Current (A)	13	21.7
Max. AC Output Current (A)	14.3	23.9
Output Power Factor	0.8 leading to 0.8 lagging	
Grid Current THD	<3% (At rated power)	
DC Injection Current (mA)	<0.5%	
Grid Frequency Range	50/60Hz (±5)	
Efficiency		
Max. Efficiency	97.5%	
Euro Efficiency	97.3%	
MPPT Efficiency	>99%	
Protection		
DC Reverse-Polarity Protection	Integrated	
AC Short Circuit Protection	Integrated	
AC Output Overcurrent Protection	Integrated	
Output Overvoltage Protection	Integrated	
Insulation Resistance Protection	Integrated	
Ground Fault Monitoring	Integrated	
Anti-islanding Protection	Integrated	
Temperature Protection	Integrated	
Integrated DC Switch	Optional	Integrated
Remote software upload	Yes	
Remote change of operating parameters	Yes	
Surge protection	DC Type II / AC Type II	
General Data		
Size (mm)	280W×272.5H×184D	330W×323H×190D
Weight (kg)	4.8	7.5
Topology	Transformerless	
Internal Consumption	<1W (Night)	
Running Temperature	-25~65°C, >45°C derating	
Ingress Protection	IP65	
Noise Emission (Typical)	≤ 35 dB	<35 dB
Cooling Concept	Natural cooling	
Max. Operating Altitude Without Derating	2000m	
Warranty	10 Years, 1 year on Accessories (Logger, ZED)	
Grid Connection Standard	IEC61727/62116, AS4777.2, CEI 0 21, C10-11, UNE217002, VDE4105, VDE0126, EN50549-1, G98, G99, NBR16149/NBR16150	
Operating Surroundings Humidity	0-100%	
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2	
Features		
DC Connection	MC-4 mateable	
AC Connection	IP65 rated plug	
Display	LCD1602	
Interface	RS485/RS232/Wifi/LAN	

*All specifications are subject to change without notice

GRID TIE INVERTER - THREE PHASE

Model	EGT-5K-3P2M		EGT-10K-3P2M	EGT-15K-3P2M
Input (DC)				
Max. DC Input Power (kW)	6.5	13		19.5
Max. DC Input Voltage (V)	1000			1000
Start-up DC Input Voltage (V)	140			250
MPPT Operating Range (V)	120~850			200~850
Max. DC Input Current (A)	13+13			13+26
Max. Short Circuit Current (A)	19.5+19.5			19.5+39
No.of MPP Trackers	2			2
No.of Strings per MPP Tracker	1			1+2
Output (AC)				
Rated Output Power (kW)	5	10		15
Max. Active Power (kW)	5.5	11		16.5
Nominal Output Voltage / Range (V)	3L/N/PE 220/380V, 230/400V			
Rated Grid Frequency (Hz)	50/60 (Optional)			
Operating Phase	Three phase			
Rated AC Grid Output Current (A)	7.6 / 7.2	15.2 / 14.5		22.7/21.7
Max. AC Output Current (A)	8.3 / 8	16.7 / 15.9		25/23.9
Output Power Factor	0.8 leading to 0.8 lagging			
Grid Current THD	<3% (At rated power)			
DC Injection Current (mA)	<0.5%			
Grid Frequency Range	50/60Hz (±5)			
Efficiency				
Max. Efficiency	98.3%			98.5%
Euro Efficiency	97.5%			
MPPT Efficiency	>99%			
Protection				
DC Reverse-Polarity Protection	Integrated			
AC Short Circuit Protection	Integrated			
AC Output Overcurrent Protection	Integrated			
Output Overvoltage Protection	Integrated			
Insulation Resistance Protection	Integrated			
Ground Fault Monitoring	Integrated			
Anti-islanding Protection	Integrated			
Temperature Protection	Integrated			
Integrated DC Switch	Integrated			
Remote software upload	Integrated			
Remote change of operating parameters	Integrated			
Surge protection	DC Type II / AC Type II			
General Data				
Size (mm)	330W×457H×185D			333W×472H×202D
Weight (kg)	10			15
Topology	Transformerless			
Internal Consumption	<1W (Night)			
Running Temperature	-25~65°C, >45°C derating			
Ingress Protection	IP65			
Noise Emission (Typical)	≤ 35 dB			<40 dB
Cooling Concept	Natural cooling			Smart cooling
Max. Operating Altitude Without Derating	2000m			
Warranty	10 Years, 1 year on Accessories (Logger, ZED)			
Grid Connection Standard	IEC61727/62116, VDE4105, UNE217002, NBR16149/NBR16150, VDE0126, AS4777.2, CEI 0 21,EN50549-1, G98, G99, C10-11			IEC 62116, IEC 61727, CEI 0-21, VDE 0126-1-1, RD 1699, C10-11, VDE-AR-N 4105, NRS 097, G99, G98
Operating Surroundings Humidity	0-100%			
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2			
Features				
DC Connection	MC-4 mateable			
AC Connection	IP65 rated plug			
Display	LCD1602			
Interface	RS485/RS232/Wifi/LAN			

*All specifications are subject to change without notice



Eastman Auto & Power Ltd.

572, Udyog Vihar, Phase-V, Gurugram, Haryana-122016, India
Email : info@eaplworld.com | Tel : +91-124-4627650 | www.eaplworld.com